



DECO|VITA
PorcelainTile

OUTDOOR
FLOOR & TILES
WALL

USER GUIDE

TECHNICAL INFORMATION



**GLAZED
PORCELAIN TILE**



**FLOOR
TILE**



**WALL
TILE**



WATER ABSORPTION
≤ 0.5%



**FROST
RESISTANT**



**INKJET
TECHNOLOGY**



**ROTOCOLOR
TECHNOLOGY**



MIN. GROUT JOINT
1 MM.



RECTIFIED

SLIP RESISTANCE VALUE

R9

Inclination angle > 6° - 10° / low static friction (Entrances, Bathrooms, Kitchens)

R10

Inclination angle > 10° - 19° / normal static friction (Storage Areas)

R11

Inclination angle > 19° - 27° / raised static friction (Restaurants, Dining Halls)

R12

Inclination angle > 27° - 35° / high static friction (Industrial Kitchens, Firefighting Buildings)

R13

Inclination angle > 35° / very high static friction (Especially on slopes and high floor wear areas)

R9 products are recommended for indoor use.
R10, R11, R12, R13 products are recommended for outdoor use.



Features

CALACATTA ----- Serie
PEARL ----- Color

2CM R11 FLAT ----- Finish

24"x24" | 102075527 | 50 faces
24"x48" | 302075527 | 25 faces

Size
Option

SKU
Number

Face
Count

PATTERN VARIATIONS

V1

The least amount of shade and texture variation.

V1

V2

Light to moderate shade and texture variation within each carton.

V2

V3

High shade texture variation within each carton.

V3

V4

Very high shade and texture variation within each carton.

V4

DECOVITA OUTDOOR PORCELAIN TILE BLENDING OF ADVANTAGES

It is a material with high technical and visual performance.

Slabs obtained by pressing, followed by vitrification: this process involves the total fusion into a single material made from natural raw materials (sand, quartz, feldspars, kaolin, clays and natural colourants) which, fired at temperatures above 1230°C (2246°F), are transformed into a product with exceptional hardness, practically no absorption at all and unmatchable mechanical characteristics.

Decovita porcelain tile is eco-compatible.

PRACTICAL CONTEMPORARY

ADHESIVE INSTALLATION

LAYING ON LAWN

LAYING ON GRAVEL

LAYING ON SAND

INSTALLATION ON RAISED PEDESTAL SYSTEM



Outdoor Series


ANDES SLATE

R11

V4

2CM

!



ANDES SLATE
MOCHA

2CM R11 RELIEF


24"x24" | 102077677 | 20 faces

R11

V4

2CM

!



ANDES SLATE
GOLD

2CM R11 RELIEF


24"x24" | 102077650 | 20 faces

R11

V4

2CM

!



ANDES SLATE
ANTHRACITE

2CM R11 RELIEF

24"x24" | 102077668 | 20 faces



AUMA

Outdoor Series



AUMA
OAK

2CM R11 FLAT

24"x48" | 302077170 | 6 faces



AUMA
TAUPE

2CM R11 FLAT

24"x48" | 302077191 | 6 faces





Outdoor Series

IPE DECKING



IPE DECKING
OAK


2CM R13 RELIEF

24"x24" | 102077570 | 7 faces



BLUESTONE

Outdoor Series



BLUESTONE
GREY

2CM R11 FLAT

24"x24" | 102067609 | 2 faces





Outdoor Series

BLUESTONE STEEL

R11

V4




BLUESTONE STEEL SLATE

2CM R11 FLAT

24"x24"
ECO102069019
1 faces

R11

V4



BLUESTONE STEEL


2CM R11 FLAT

24"x24"
ECO102069029
1 faces



CALACATTA

Outdoor Series



CALACATTA PEARL

2CM R11 FLAT

24"x24" | 102075527 | 50 faces

24"x48" | 302075527 | 25 faces



CALACATTA SLATE PEARL

2CM R11 FLAT

24"x24" | 102078427 | 50 faces





Outdoor Series


CALACATTA

R11

V4

2CM

FLAT



**CALACATTA
GOLD**

2CM R11 FLAT


24"x24" | 102077050 | 30 faces

R11

V4

2CM

FLAT



**CALACATTA
SLATE
GOLD**

2CM R11 FLAT

24"x24" | 102078450 | 30 faces



CLAY

Outdoor Series



CLAY ANTHRACITE

2CM R11 FLAT

24"x24" | 102067468 | 10 faces

24"x48" | 302067468 | 5 faces



CLAY GREY

2CM R11 FLAT

24"x24" | 102067409 | 10 faces

24"x48" | 302067409 | 5 faces





Outdoor Series


CLAY

R11

V4

10

5



CLAY
SAND

2CM R11 FLAT

24"x24" | 102067458 | 10 faces


24"x48" | 302067458 | 5 faces

R11

V4

10

5



CLAY
WHITE

2CM R11 FLAT

24"x24" | 102067410 | 10 faces



CLAY FULL BULLNOSE

Outdoor Series

V2



**CLAY
FULL BULLNOSE**
ANTHRACITE

2CM R11 FLAT

24"x48" | 302023868 | 5 faces

V2



**CLAY
FULL BULLNOSE**
GREY

2CM R11 FLAT

24"x48" | 302023809 | 5 faces



CLAY FULL BULLNOSE

Outdoor Series




**CLAY
FULL BULLNOSE**
WHITE

2CM R11 FLAT

24"x48" | 302023810 | 5 faces

*Easy to apply different size
and surface options to
reduce sharpness at pool
and stair edges.*



20mm

FULL BULLNOSE




CROSSOVER

Outdoor Series

R11

V4




CROSSOVER CREMA

2CM R11 FLAT

24"x24"
ECO102069101
12 faces

R11

V4



CROSSOVER WHITE

2CM R11 FLAT

24"x24" | 102067759 | 12 faces
24"x48" | 302067759 | 6 faces





Outdoor Series

CROSSOVER



CROSSOVER GREY

2CM R11 FLAT

24"x24" | 102067709 | 12 faces



CROSSOVER ANTHRACITE

2CM R11 FLAT

24"x24" | 102067768 | 12 faces



EARTH

Outdoor Series



EARTH GREY

2CM R11 FLAT

24"x24" | 102068309 | 14 faces

24"x48" | 302068309 | 7 faces



EARTH ANTHRACITE

2CM R11 FLAT


24"x24" | 102068368 | 14 faces





Outdoor Series

EPIRO



EPIRO ANTHRACITE

2CM R11 FLAT

24"x24" | 102068168 | 12 faces
24"x48" | 302068168 | 6 faces



EPIRO GREY

2CM R11 FLAT

24"x24" | 102068109 | 16 faces
24"x48" | 302068168 | 8 faces



SUDBURY

Outdoor Series



SUDBURY ANHRACITE

2CM R11 FLAT

24"x24" | 102072468 | 6 faces



SUDBURY LIGHT GREY

2CM R11 FLAT

24"x24" | 102072438 | 6 faces





Outdoor Series

SANDROCK

R11

V4

ECO

1 face



SANDROCK SILVER


2CM R11 FLAT

24"x24"
ECO102069100
1 faces



QUARRY

Outdoor Series



QUARRY GREY

2CM R11 FLAT

24"x24"
ECO102069079
1 faces



BOX / PALLET DETAILS

NOMINAL THICKNESS		NOMINAL SIZE		PCS / BOX	BOX		BOX PER PALLET	PALLET		PALLET SIZE		WEIGHT OF LOADED PALLET	
cm	inch	cm	inch		m ²	sqf		m ²	sqf	cm	inch	kg	lb
2	3/4"	60x60	24x24	2	0.72	7.74	30	21.60	232.41	80x120x75	31x48x29	1,150	2,530
2	3/4"	60x120	24x48	1	0.72	7.74	32	23.04	247.91	93x128x75	36x50x29	1,250	2,750
1 inch = 2.54 cm		1 cm = 0.39 Inch		1 lb = 0.45 Kg		1 kg = 2.20 lb		1 m ² = 10.76 sf		1 sf = 0.09 m ²			

** Decovita USA provides Freight Service if required, by LTL needed.

For more details and delivery for different locations please contact to Sales Representative.

DECOVITA OUTDOOR 2 CM

Method	Declared Value
The ASTM C373 Water Absorption	≤ 0.3 %
The ASTM C648 Breaking Strength	≥ 2200 lbf
The ASTM C650 Chemical Resistance	Resistant
The ASTM C1026 Freeze-Thaw	Resistant
The ASTM C1027 Surface Abrasion (PEI)	Min Class 4
The ASTM C1378 Stain Resistance	Min Class B
ANSI A326.3 Dynamic Coefficient of Friction (DCOF – wet only)	≥ 0.79
ASTM 1895 Mohs Scratch Hardness	Min 7
Length and width	± 0.15%
Thickness	± 0.5%
Straightness of Sides	± 10 %
Rectangularity	± % 0.25 (± 1 mm)
Center-Edge Curvature-Warpage	± % 0.25 (± 1 mm)
Surface Quality	% 95

DECO|VITA PorcelainTile

USA HEADQUARTERS & VIRGINIA SALES and DISTRIBUTION CENTER

22675 Dulles Summit Ct Suite 125 Sterling VA 20166 Office: (+1) 571 926 8326
Monday - Friday: 8:00 AM - 5:00 PM Saturday-Sunday: Closed

CALIFORNIA SALES and DISTRIBUTION CENTER

1623-1625 S. Sunkist St. Anaheim, CA 92806 Office: (+1) 714 406 1500
Monday - Friday: 8:00 AM - 5:00 PM Saturday-Sunday: Closed

TEXAS SALES and DISTRIBUTION CENTER

5870 W. Fuqua St Suite #100 77085 Houston Texas Office: (+1) 281 915 0884
Monday - Friday: 8:00 AM - 5:00 PM Saturday-Sunday: Closed

www.decovitausa.com